

# **PERMASEAL 2500**

## **TECHNICAL INFORMATION**

### **Description:**

Permaseal 2500 is a specially formulated solvent acrylic lacquer designed to meet the application demands of the decorative concrete finishing industry where very high gloss levels are required beyond the levels obtained by standard sealers. Once cured the film forms a tough protective coating which both protects and highlights the colours in the finish.

### **Suitability:**

Permaseal 2500 is recommended for use on Stencil Concrete and Flo Crete surfaces where a thicker lacquer is required due to the porous nature of the surface.

### **Typical Properties:**

<b>Appearance</b>	<b>Thin clear solvent based liquid</b>
<b>Solids Content</b>	<b>Approx 25 - 26 %</b>

### **Method of application:**

Permaseal 2500 is designed to be both spray and broom applied. Best results are obtained by putting down two coats with adequate drying time between. Additionally improved penetration of the first coat can be obtained by the addition of approx 15 % Solvent (SL05 to SL200). Improved penetration is desirable as the product is relatively high in both solids and viscosity.

**Rotate stock and protect from freezing.**

**THE INFORMATION PRESENTED IS BELIEVED TO BE ACCURATE. HOWEVER, NO GUARANTEE IS IMPLIED OR GIVEN. USER'S SHOULD CONDUCT THERE OWN TESTING TO DETERMINE THE SUITABILITY OF ANY PRODUCT FOR A PARTICULAR PURPOSE.**