

SAFETY DATA SHEET

Issue Date 7-Nov-2019

Version 1

Section 1: PRODUCT IDENTIFIER AND CHEMICAL IDENTITY

Product identifier

Product Name Permaseal 2500

Product description Acrylic resin

Other means of identification

UN Number UN1866

Recommended use of the chemical and restrictions on use

Recommended Use Recommended for Industrial and/or Professional use only

Details of manufacturer or importer

Manufacturer

Permacolour Australia PTY LTD
46 Moss Street, Slacks Creek
4127, QLD, Australia

For further information, please contact

Contact Point +61 (07) 3290 2064

E-mail address mail@permacolour.com.au

Emergency telephone number

Emergency telephone number +61 (07) 3290 2064 (Forwarding number enabled 24/7)

Section 2: HAZARD(S) IDENTIFICATION

Classified as dangerous goods in accordance with the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG)

Classified as a hazardous substance in accordance with the criteria of Safe Work Australia - Globally Harmonised System (GHS)

GHS Classification

Flammable liquids	Category 3 - (H226)
Acute toxicity - Inhalation (Dusts/Mists)	Category 4 - (H332)
Skin corrosion/irritation	Category 2 - (H315)
Specific target organ toxicity (single exposure)	Category 3 - (H335)
Specific target organ toxicity (repeated exposure)	Category 2 - (H373)

Label elements



Signal word

Warning

Hazard statements

H226 - Flammable liquid and vapour

H332 - Harmful if inhaled

Permaseal 2500

H315 - Causes skin irritation

H373 - May cause damage to organs through prolonged or repeated exposure

H335 - May cause respiratory irritation

Precautionary Statements - Prevention

Use only outdoors or in a well-ventilated area

Wash face, hands and any exposed skin thoroughly after handling

Wear protective gloves/protective clothing/eye protection/face protection

Do not breathe dust/fume/gas/mist/vapours/spray

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Use explosion-proof electrical/ ventilating/ lighting/ equipment

Keep cool

Precautionary Statements - Response

Specific treatment (see supplemental first aid instructions on this label)

Get medical advice/attention if you feel unwell

If skin irritation occurs: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before re-use

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTRE or doctor/physician if you feel unwell

In case of fire: Use CO₂, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other hazards

May be harmful in contact with skin

Harmful to aquatic life with long lasting effects

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

Substance

Not applicable

Mixture

<u>Chemical Name</u>	<u>CAS No</u>	<u>Weight-%</u>
Xylene	1330-20-7	30-<60
Solvent naphtha (petroleum), light aromatic	64742-95-6	10-<25
Ethylbenzene	100-41-4	10-<20
Non-hazardous ingredients	Balance	

Section 4: FIRST AID MEASURES

Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
Emergency telephone number	Poisons Information Centre, Australia: 13 11 26
Inhalation	Remove to fresh air. IF exposed or concerned: Get medical advice/attention. Get medical

Permaseal 2500

attention immediately if symptoms occur.

Skin contact

Wash off immediately with soap and plenty of water for at least 15 minutes. Get medical attention if irritation develops and persists.

Eye contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

Do NOT induce vomiting. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Call a doctor.

Self-protection of the first aider

Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Wear personal protective clothing (see section 8). Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms

Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Burning sensation. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Indication of any immediate medical attention and special treatment needed

Note to doctors

Because of the danger of aspiration, emesis or gastric lavage should not be used unless the risk is justified by the presence of additional toxic substances.

Section 5: FIRE FIGHTING MEASURES

Suitable Extinguishing Media

Suitable extinguishing media

Carbon dioxide (CO₂). Dry chemical. Alcohol resistant foam. Water spray.

Unsuitable extinguishing media

Do not use water jetstream

Specific hazards arising from the chemical

Flammable. Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective actions for fire-fighters

Wear self-contained breathing apparatus and protective suit. Use personal protective equipment as required.

Hazchem code

•3Y.

Section 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions

Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.

Permaseal 2500

Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

For emergency responders

Use personal protection recommended in Section 8.

Environmental precautions

Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

Methods and material for containment and cleaning up

Methods for containment

Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

Methods for cleaning up

Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled containers.

Precautions to prevent secondary hazards

Prevention of secondary hazards

Clean contaminated objects and areas thoroughly observing environmental regulations.

Reference to other sections

See section 8 for more information. See section 13 for more information.

Section 7: HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

Use personal protection equipment. Avoid contact with skin and eyes. Avoid breathing vapours or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharges. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before re-use.

General Hygiene Considerations

When using do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Wash hands before breaks and immediately after handling the product. Wash hands before breaks and after work. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e. pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children. Store away from other materials.

Incompatible materials

Strong acids. Strong bases. Strong oxidising agents.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Permaseal 2500

Control parameters

Exposure Limits . This product, as supplied, contains hazardous materials with occupational exposure limits.

Chemical Name	Australia
Xylene 1330-20-7	80 ppm TWA 350 mg/m ³ TWA 150 ppm STEL 655 mg/m ³ STEL
Ethylbenzene 100-41-4	100 ppm TWA 434 mg/m ³ TWA 125 ppm STEL 543 mg/m ³ STEL

Biological occupational exposure limits An occupational medicine specialist familiar with national and regional regulations and standards must be consulted to establish a program of medical examinations for workers exposed to substances with biological limit values

Chemical Name	Australia	ACGIH	United Kingdom	European Union
Xylene 1330-20-7	-	Methylhippuric acids: 1.5 g/g creatinine urine end of shift	650 mmol/mol creatinine	
Ethylbenzene 100-41-4	-	Sum of mandelic acid and phenylglyoxylic acid: 0.15 g/g creatinine urine end of shift	-	

Appropriate engineering controls

Engineering Controls Ensure adequate ventilation, especially in confined areas.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles. Face protection shield.

Skin and body protection Antistatic footwear. Wear fire/flame resistant/retardant clothing. Gloves made of plastic or rubber. Suitable protective clothing. Apron.

Respiratory protection Where respiratory protection is required, use a respirator selected and in accordance with AS/NZS 1715 and AS/NZS 1716.

Environmental exposure controls Do not allow into any sewer, on the ground or into any body of water.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state liquid
Appearance clear viscous
Colour clear
Odour Aromatic Petroleum distillates
Odour threshold No information available

Property	Values	Remarks • Method
pH		No information available
Melting point / freezing point		No information available
Boiling point / boiling range	137 - 143 °C	(based on components)
Flash point	27 °C	Derived from solvent Tag Closed Cup

Permaseal 2500

Evaporation rate	0.7	
Flammability (solid, gas)		No information available
Flammability Limit in Air		
Upper flammability limit:	7.7 %	
Lower flammability limit:	1.1 %	
Vapour pressure	52	hPa, 40°C Derived from solvent
Vapour density	3.7	Derived from solvent
Relative density	0.91	
Water solubility		Insoluble
Solubility(ies)	-	No information available
Partition coefficient		No information available
Autoignition temperature	465 °C	Derived from solvent
Decomposition temperature		No information available
Kinematic viscosity	60 mm ² /s	
Dynamic viscosity	55 - 65 mPa s	No information available
Explosive properties	No information available	
Oxidising properties	No information available	

Other Information

VOC Content (%)	No information available
Density	No information available

* This information may be derived from the components in the preparation.

Section 10: STABILITY AND REACTIVITY

Reactivity

No Data Available.

Chemical stability

Stable under normal conditions.

Explosion data

Sensitivity to Mechanical Impact	None.
Sensitivity to Static Discharge	May be ignited by heat, sparks or flames.

Possibility of Hazardous Reactions

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong acids. Strong bases. Strong oxidising agents.

Hazardous Decomposition Products

None under normal use conditions.

Section 11: TOXICOLOGICAL INFORMATION

Acute toxicity

Information on likely routes of exposure

Product Information

Permaseal 2500

Inhalation	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.
Eye contact	Specific test data for the substance or mixture is not available. Irritating to eyes. (based on components). Causes serious eye irritation.
Skin contact	Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components).
Ingestion	Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document

Converted acute toxicity point estimates may have been used when only acute toxicity hazard classification is available.

ATEmix (oral)	6,546.00
ATEmix (dermal)	2,572.00
ATEmix (inhalation-vapour)	21.00
ATEmix (inhalation-dust/mist)	2.80

2E-05% of the mixture consists of ingredient(s) of unknown toxicity

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Xylene	= 3500 mg/kg (Rat)	-	= 29.08 mg/L (Rat) 4 h = 5000 ppm (Rat) 4 h
Solvent naphtha (petroleum), light aromatic	= 8400 mg/kg (Rat)	-	= 3400 ppm (Rat) 4 h
Ethylbenzene	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.2 mg/L (Rat) 4 h

See section 16 for terms and abbreviations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation

Classification based on individual ingredients of the mixture. Irritating to skin.

Serious eye damage/eye irritation

Classification based on individual ingredients of the mixture. Irritating to eyes.

Sensitisation

No information available.

Germ cell mutagenicity

No information available.

Carcinogenicity

.

Reproductive toxicity

No information available.

STOT - single exposure

May cause respiratory irritation. May cause drowsiness or dizziness.

STOT - repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard

No information available.

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity

Unknown Aquatic Toxicity 0% of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical Name	Fish
Xylene	13.4 mg/L LC50 96 h Pimephales promelas flow-through 13.5 - 17.3 mg/L LC50 96 h Oncorhynchus mykiss 13.1 - 16.5 mg/L LC50 96 h Lepomis macrochirus flow-through 23.53 - 29.97 mg/L LC50 96 h Pimephales promelas static 19 mg/L LC50 96 h Lepomis macrochirus 2.661 - 4.093 mg/L LC50 96 h Oncorhynchus mykiss static 30.26 - 40.75 mg/L LC50 96 h Poecilia reticulata static 780 mg/L LC50 96 h Cyprinus carpio semi-static 780 mg/L LC50 96 h Cyprinus carpio 7.711 - 9.591 mg/L LC50 96 h Lepomis macrochirus static
Solvent naphtha (petroleum), light aromatic	9.22 mg/L LC50 96 h Oncorhynchus mykiss
Ethylbenzene	11.0 - 18.0 mg/L LC50 96 h Oncorhynchus mykiss static 7.55 - 11 mg/L LC50 96 h Pimephales promelas flow-through 9.1 - 15.6 mg/L LC50 96 h Pimephales promelas static 9.6 mg/L LC50 96 h Poecilia reticulata static 4.2 mg/L LC50 96 h Oncorhynchus mykiss semi-static 32 mg/L LC50 96 h Lepomis macrochirus static

Chemical Name	Crustacea
Xylene	3.82 mg/L EC50 48 h water flea 0.6 mg/L LC50 48 h Gammarus lacustris
Solvent naphtha (petroleum), light aromatic	6.14 mg/L EC50 48 h Daphnia magna
Ethylbenzene	1.8 - 2.4 mg/L EC50 48 h Daphnia magna

Chemical Name	Algae/aquatic plants
Ethylbenzene	438 mg/L EC50 96 h Pseudokirchneriella subcapitata 4.6 mg/L EC50 72 h Pseudokirchneriella subcapitata 1.7 - 7.6 mg/L EC50 96 h Pseudokirchneriella subcapitata static 2.6 - 11.3 mg/L EC50 72 h Pseudokirchneriella subcapitata static

Persistence and degradability

No information available.

Bioaccumulative potential

Chemical Name	Partition coefficient
Xylene	3.15
Ethylbenzene	3.118

Mobility

Mobility in soil

No information available.

Mobility

No information available.

Permaseal 2500

Other adverse effects

No information available.

Section 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from residues/unused products

Hazardous wastes must be transported by a licensed hazardous waste transporter and disposed of or treated in a licensed hazardous waste treatment, storage, disposal or recycling facility.

Contaminated packaging

Disposal should be in accordance with applicable regional, national and local laws and regulations. Observe all label precautions until container is cleaned, reconditioned or destroyed. Refer to all federal, state and local regulations prior to disposal of container and unused contents by reuse, recycle or disposal.

Section 14: TRANSPORT INFORMATION

ADG

UN Number	UN1866
Proper shipping name	Resin solution
Description	UN1866, Resin solution, 3, III
Hazard Class	3
Packing Group	III
Special Provisions	223, *
Hazchem code	•3Y.
IERG	14

IMDG

UN/ID no	UN1866
Proper shipping name	Resin solution
Description	UN1866, Resin solution, 3, III, (27°C c.c.)
Hazard Class	3
Packing Group	III
EmS-No	F-E, S-E
Special Provisions	223, 955

Transport in bulk according to Annex II of MARPOL 73/78

No information available

IATA

UN/ID no	UN1866
Proper shipping name	Resin solution
Description	UN1866, Resin solution, 3, III
Hazard Class	3
Packing Group	III
ERG Code	3L

Section 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Australia

Classified as dangerous goods in accordance with the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG). Classified as a hazardous substance in accordance with the criteria of Safe Work Australia - Globally Harmonised System (GHS)

See section 8 for national exposure control parameters

Permaseal 2500

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Classified as a scheduled poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Poison Schedule Number	S6
Major hazard (accident/incident planning) regulation	Verify that license requirements are met
Hazardous chemical category	<u>Threshold quantity (T)</u>
Liquids that meet the criteria for Class 3 Packing Group II or III	50 000
Liquids with flash points <61°C kept above their boiling points at ambient conditions	200

International Inventories

AICS - Australian Inventory of Chemical Substances	No information available
DSL - Canadian Domestic Substances List	No information available
IECSC - China Inventory of Existing Chemical Substances	No information available
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances	No information available
ENCS - Japan Existing and New Chemical Substances	No information available
KECL - Korean Existing and Evaluated Chemical Substances	No information available
NZIoC - New Zealand Inventory of Chemicals	No information available
PICCS - Philippines Inventory of Chemicals and Chemical Substances	No information available
CICR - Turkey Chemical Inventory Control Regulation	No information available
NCSR - Taiwan National Chemical Substance Registry	No information available
TSCA - United States Toxic Substances Control Act Section 8(b) Inventory	No information available

For confirmation on the European REACH status contact the Nuplex Regional Compliance group for additional information

International Regulations

Ozone-depleting substances (ODS) Not applicable

Persistent Organic Pollutants Not applicable

Export Notification requirements Not applicable

Section 16: ANY OTHER RELEVANT INFORMATION

Revision Date 7-Nov-2024

Revision Note

The symbol (*) in the margin of this SDS indicates that this line has been revised.

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation
C	Carcinogen		

Disclaimer

This information is given without any warranty or representation. We do not assume any legal responsibility for same, nor do we give permission, inducement, or recommendation to practice any patented invention without a license. It is offered solely for your consideration, investigation, and verification. Before using any product, read its label.

End of Safety Data Sheet